

View Online at <https://aerobasegroup.com/nsn/5930-01-105-5091>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Corrosion resistant

Body Diameter:

1.000 inches

Bushing Length:

1.000 inches

Body Length:

0.980 inches

Actuator Style:

Round

Actuator Diameter:

0.250 inches

Actuator Height:

0.375 inches

Actuator Free Position Height:

1.375 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Switch Release Force:

64.0 ounces

Switch Actuating Force:

134.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 4.000 amperes motor dc

Special Features:

Wire leads 24.000 in. Lg

Thread Series Designator:

Unef

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0