

View Online at <https://aerobasegroup.com/nsn/5930-01-106-0761>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Overall Length:

1.550 inches

First Flat Length:

0.312 inches single actuator

Flat Height:

0.218 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.375 inches single actuator

Overall Diameter:

1.180 inches

Nonturn Device Radius:

0.375 inches at 3:00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 3:00 o'clock

Operating Temperature Range:

+70.0/+160.0 degrees fahrenheit

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

2 single section rear

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

68.5 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Clip

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Precious Material And Location:

Clips and rotor blades silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0