

View Online at <https://aerobasegroup.com/nsn/5930-01-106-3686>

Thread Class:

2a single mounting facility

Thread Length:

0.380 inches single mounting facility

Overall Length:

1.670 inches

Shaft Diameter:

0.247 inches single actuator and 0.251 inches single actuator

Shaft Length:

0.370 inches single actuator

Nonturn Device Radius:

0.370 inches at 5: 00 o'clock and 0.380 inches at 5: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 5: 00 o'clock

Operating Temperature Range:

-65.0/+85.0 degrees celsius

End Application:

An/tyq-3a

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

30.0 dc at sea level

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Detent Rotational Torque Range:

+12.000/+18.000 inch-ounces single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

50.0 milliamperes resistive load ac at sea level

Precious Material And Location:

Contacts and rotor blades silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0