

View Online at <https://aerobasegroup.com/nsn/5930-01-106-4548>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Waterproof

**Overall Length:**

2.900 inches

**Overall Height:**

0.940 inches

**Overall Width:**

0.660 inches

**Bushing Length:**

0.620 inches

**Body Length:**

0.940 inches

**Body Width:**

0.660 inches

**Body Height:**

1.170 inches

**Case Material:**

Metal

**Actuator Length:**

0.730 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.840 inches

**Actuator Width:**

0.730 inches

**Actuator Color:**

White single actuator

**Illuminated Actuator Color:**

White single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thread Size:**

0.625 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

**Test Data Document:**

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

6 connector, receptacle

**Specification Data:**

81349-mil-s-22885/81 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0