NSN 5930-01-106-7593

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-106-7593

Thread Length:
0.906 inches single pressure connection
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
2.562 inches
Outside Diameter:
0.250 inches single connection
Overall Height:
4.094 inches
Overall Width:
1.469 inches
Mounting Slot Width:
0.219 inches
Body Height:
1.906 inches
Distance Between Mounting Facility Centers:
1.750 inches
End Application:
5840-01-020-5631 radar set
Pressure Switch Type:
Gage
Mounting Method:
Bracket and slot
Contact Action Stimulus:
Increase
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
15.0 amperes resistive load second voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+3.00/+30.00 actuation point pounds per square inch and +1.00/+28.00 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point knob and external actuation point knob

NSN 5930-01-106-7593

Pressure Switch - Page 2 of 2



Contact Voltage Rating In Volts:

250.0 ac at sea level second voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Gas

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0