NSN 5930-01-106-7593

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-106-7593

Thread Length:

0.906 inches single pressure connection

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

2.562 inches

Outside Diameter:

0.250 inches single connection

Overall Height:

4.094 inches

Overall Width:

1.469 inches

Mounting Slot Width:

0.219 inches

Body Height:

1.906 inches

Distance Between Mounting Facility Centers:

1.750 inches

End Application:

5840-01-020-5631 radar set

Pressure Switch Type:

Gage

Mounting Method:

Bracket and slot

Contact Action Stimulus:

Increase

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

15.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+3.00/+30.00 actuation point pounds per square inch and +1.00/+28.00 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point knob and external actuation point knob

NSN 5930-01-106-7593

Pressure Switch - Page 2 of 2



Contact Voltage Rating In Volts:

250.0 ac at sea level second voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Gas

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A048b0