

View Online at <https://aerobasegroup.com/nsn/5930-01-107-6494>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.250 inches single mounting facility

**Overall Length:**

4.390 inches

**Overall Height:**

1.531 inches

**Overall Width:**

1.406 inches

**Shaft Diameter:**

0.250 inches 1st actuator

**Shaft Length:**

0.469 inches 1st actuator

**Nonturn Device Radius:**

0.531 inches at 8: 00 o'clock

**Individual Section Quantity:**

2

**Nonturn Device Type:**

Pin at 8: 00 o'clock

**Operating Temperature Range:**

-25.0/+85.0 degrees celsius

**End Application:**

6625-00-041-0095

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 2nd section front

**Throw Quantity:**

5 2nd section front

**Mounting Method:**

Threaded bushing single mounting facility

**Features Provided:**

Variable resistor provisions

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

5 1st actuator

**Shaft Type:**

Round, hollowed 1st actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes 2nd section front

**Switch Actuator Positioning Increment:**

45.0 degrees 1st actuator

**Switch Actuator Stop Device Type:**

Fixed stop 1st actuator

**Contact Load Current Rating:**

500.0 milliamperes resistive load ac at sea level

**Precious Material And Location:**

Contact surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0