

View Online at <https://aerobasegroup.com/nsn/5930-01-107-6495>

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Overall Length:

2.615 inches

Overall Height:

1.531 inches

Overall Width:

1.375 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.469 inches single actuator

Nonturn Device Radius:

0.531 inches at 8: 00 o'clock

Individual Section Quantity:

4

Nonturn Device Type:

Pin at 8: 00 o'clock

Operating Temperature Range:

-25.0/+85.0 degrees celsius

End Application:

6625-00-041-0095

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 4th section rear

Throw Quantity:

9 3rd section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Rotor Through Connection Quantity:

1 2nd section

Switch Actuator Indexing Position Quantity:

9 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes 2nd section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load ac at sea level

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0