NSN 5930-01-107-6717

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-107-6717

Darle Otale
Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Watertight and corrosion resistant
Overall Length:
5.750 inches
Overall Height:
2.740 inches
Overall Width:
1.870 inches
Case Material:
Metal
Actuator Style:
Roller arm
Actuator Roller Diameter:
0.750 inches
Actuator Roller Width:
0.320 inches
Housing Height:
1.780 inches
Housing Length:
5.750 inches
Housing Width:
1.870 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
3.750 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.410 inches
Maximum Voltage Rating In Volts:
440.0 ac
End Application:
Multi-hull 03950
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded hole
Nonpile-up Contact Arrangement:
2 two circuit, two positions momentary single switch unit
Switch Release Force:
2.0 ounces

Actuator Movement:

50.0 pretravel degrees and 4.0 overtravel degrees and 10.0 differential degrees

NSN 5930-01-107-6717

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:
4.500 amperes resistive ac
Special Features:
Lever with clockwise and counterclockwise trip
Terminal Type And Quantity:
8 screw
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No Fiig: A053a0