

View Online at <https://aerobasegroup.com/nsn/5930-01-107-6717>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight and corrosion resistant

Overall Length:

5.750 inches

Overall Height:

2.740 inches

Overall Width:

1.870 inches

Case Material:

Metal

Actuator Style:

Roller arm

Actuator Roller Diameter:

0.750 inches

Actuator Roller Width:

0.320 inches

Housing Height:

1.780 inches

Housing Length:

5.750 inches

Housing Width:

1.870 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

3.750 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.410 inches

Maximum Voltage Rating In Volts:

440.0 ac

End Application:

Multi-hull 03950

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded hole

Nonpile-up Contact Arrangement:

2 two circuit, two positions momentary single switch unit

Switch Release Force:

2.0 ounces

Actuator Movement:

50.0 pretravel degrees and 4.0 overtravel degrees and 10.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

4.500 amperes resistive ac

Special Features:

Lever with clockwise and counterclockwise trip

Terminal Type And Quantity:

8 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0