## NSN 5930-01-107-6719

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-107-6719

Body Style:
Bushing/hole mounted
Overall Length:
0.780 inches
Overall Height:
1.120 inches
Overall Width:
0.375 inches
Bushing Length:
0.370 inches
Body Length:
0.780 inches
Body Width:
0.375 inches
Body Height:
0.660 inches
Case Material:
Plastic
Actuator Style:
Round
Actuator Diameter:
0.156 inches
Actuator Height:
0.090 inches
Actuator Free Position Height:
0.460 inches
Actuator Adapter Style:
Pushbutton
Adapter Bushing Length:
0.370 inches
Maximum Voltage Rating In Volts:
250.0 ac and 30.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Thready Qty Per Inch (tpi):
40
Thread Size:
0.250 inches
Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

## **NSN 5930-01-107-6719** Sensitive Switch - Page 2 of 2



Switch Release Force:
1.0 ounces
Switch Actuating Force:
12.0 ounces
Actuator Movement:
0.030 pretravel inches and 0.005 overtravel inches and 0.004 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 3.000 amperes inductive dc and 10.000 amperes resistive ac and 10.000 amperes inductive ac
Precious Material And Location:
Contacts silver
Thread Series Designator:
Uns
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A053a0