

View Online at <https://aerobasegroup.com/nsn/5930-01-107-8890>

Thread Class:

2a single mounting facility

Thread Length:

0.522 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

1.884 inches

Overall Diameter:

1.575 inches

Individual Section Quantity:

1

End Application:

F16 aircombf1t 81755

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section periphery

Throw Quantity:

2 single section periphery

Mounting Method:

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

1.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

2 single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section periphery

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load ac at sea level and 2.0 amperes inductive load ac at sea level

Special Features:

Key operated; key withdrawal position a only

Style Designator:

Miniature, bushing mount

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0