

View Online at <https://aerobasegroup.com/nsn/5930-01-108-6857>

Thread Class:

3a single threaded bushing

Body Diameter:

0.665 inches

Body Length:

1.500 inches

Temperature Sensing Element Type:

Internal sensor

Width Across Flats:

1.000 inches

Operating Temperature Rating:

400.0 degrees fahrenheit

Mounting Method:

Threaded bushing

Features Provided:

Hermetically sealed case

Thready Qty Per Inch (tpi):

16 single threaded bushing

Contact Action Stimulus:

Increase

Thread Size:

0.750 inches single threaded bushing

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

2.0 amperes resistive load second voltage and 1.0 amperes inductive load second voltage and 1.0 amperes lamp load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

5.00 differential point degrees fahrenheit and 165.00 actuation point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Frequency In Hertz:

60.0 first voltage

Thread Series Designator:

Unf single threaded bushing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0

Mil-std (military Standard):

Mil-prf-24236 spec.