

View Online at <https://aerobasegroup.com/nsn/5930-01-108-7113>

Thread Class:

2b all threaded hole

Hazardous Locations/environmental Protection:

Dustproof and explosion proof

Overall Length:

Between 2.500 inches and 3.270 inches

Overall Height:

2.510 inches

Overall Width:

2.400 inches

Body Length:

Between 2.500 inches and 3.270 inches

Body Height:

2.420 inches

Operating Temperature Rating:

Between 32.0 degrees fahrenheit and 185.0 degrees fahrenheit

Mounting Method:

Line and threaded hole

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Thread Size:

0.563 inches all threaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

3.0 amperes inductive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

0.65 actuation point gallons per minute and 0.45 deactuation point gallons per minute and 0.20 differential point gallons per minute

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Media For Which Designed:

Gas

Style Designator:

Rectangular

Test Data Document:

81349-mil-s-28788 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unf all threaded hole

Specification Data:

81349-mil-s-28788/1 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0