

View Online at <https://aerobasegroup.com/nsn/5930-01-108-8528>

Hazardous Locations/environmental Protection:

Moisture proof

Overall Length:

5.656 inches

Overall Height:

5.297 inches

Overall Width:

2.094 inches

Mounting Slot Width:

0.375 inches

Body Height:

3.250 inches

Unthreaded Mounting Hole Diameter:

0.203 inches

Longest Horizontal Distance Between Mounting Centers:

4.984 inches

Intermediate Horizontal Distance Between Mounting Centers:

1.562 inches

Longest Vertical Distance Between Mounting Centers:

1.000 inches

End Application:

4120-01-080-2850

Pressure Switch Type:

Differential

Mounting Method:

Slot and unthreaded hole and threaded hole

Features Provided:

Capillary tube end seal connection

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Four position parallelogram

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

10.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

16.00 actuation point pound and 11.00 deactuation point pound

Contact Voltage Rating In Volts:

24.0 dc at sea level single voltage

Media For Which Designed:

Liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0