

View Online at <https://aerobasegroup.com/nsn/5930-01-108-8529>

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

7.750 inches

Overall Height:

6.531 inches

Unthreaded Mounting Hole Diameter:

0.343 inches

Longest Horizontal Distance Between Mounting Centers:

4.000 inches

End Application:

Test bed trai 73342

Pressure Switch Type:

Gage

Mounting Method:

Base and unthreaded hole

Features Provided:

Electrical access port and tamper proof cap

Thready Qty Per Inch (tpi):

14 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

160.00 pounds per square inch

Thread Size:

0.500 inches single pressure connection

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

10.0 amperes inductive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+3.90/+80.00 actuation point pounds per square inch and +0.50/+76.60 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

480.0 ac at sea level first voltage

Pressure Connector Type:

Swivel nut, gasket seal, threaded internal single connection

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0