

View Online at <https://aerobasegroup.com/nsn/5930-01-108-9474>

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

7.500 inches

Overall Width:

4.062 inches

Body Diameter:

3.719 inches

Mounting Slot Width:

0.344 inches

Distance Between Mounting Facility Centers:

3.500 inches

End Application:

4920-01-039-2891

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -20.0 degrees celsius and 60.0 degrees celsius

Mounting Method:

Bracket and slot

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

500.0 milliamperes resistive load fourth voltage

Contact Adjustability:

Deactuation point not adjustable, manual reset and actuation point adjustable

Contact Adjustment Range:

+6.00/+200.00 actuation point pounds per square inch gage

Contact Adjustment Type:

External actuation point knob

Contact Stimulus Rating:

5.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

250.0 dc at sea level third voltage

Pressure Connector Type:

Plain, threaded internal single connection

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0