## NSN 5930-01-108-9474

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-108-9474

Hazardous Locations/environmental Protection:
Watertight
Overall Length:
7.500 inches
Overall Width:
4.062 inches
Body Diameter:
3.719 inches
Mounting Slot Width:
0.344 inches
Distance Between Mounting Facility Centers:
3.500 inches
End Application:
4920-01-039-2891
Pressure Switch Type:
Gage
Operating Tempurature Rating:
Between -20.0 degrees celsius and 60.0 degrees celsius
Mounting Method:
Bracket and slot
Thready Qty Per Inch (tpi):
18 single pressure connection
Contact Action Stimulus:
Increase
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
500.0 milliamperes resistive load fourth voltage
Contact Adjustability:
Deactuation point not adjustable, manual reset and actuation point adjustable
Contact Adjustment Range:
+6.00/+200.00 actuation point pounds per square inch gage
Contact Adjustment Type:
External actuation point knob
Contact Stimulus Rating:
5.00 differential point pounds per square inch gage

## NSN 5930-01-108-9474

Pressure Switch - Page 2 of 2



250.0 dc at sea level third voltage

**Pressure Connector Type:** 

Plain, threaded internal single connection

**Thread Series Designator:** 

Npt single pressure connection

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A048b0