## NSN 5930-01-109-0759

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-109-0759

| Hazardous Locations/environmental Protection:   |
|---|
| Vibration resistant   |
| Overall Length:   |
| 3.000 inches  |
| Overall Width:  |
| 1.960 inches  |
| Body Diameter:  |
| 1.390 inches  |
| Body Length:  |
| 1.690 inches  |
| Unthreaded Mounting Hole Diameter:  |
| 0.201 inches  |
| Distance Between Mounting Facility Centers:   |
| 0.500 inches  |
| Pressure Switch Type:   |
| Gage  |
| Mounting Method:  |
| Bracket and unthreaded hole   |
| Contact Action Stimulus:  |
| Increase  |
| Mounting Facility Pattern:  |
| Two position in-line  |
| Nonpile-up Contact Arrangement:   |
| 1 pole, double throw, one position momentary  |
| Terminal Type:  |
| Connector, receptacle   |
| Contact Load Current Rating:  |
| 5.0 amperes resistive load single voltage and 2.5 amperes inductive load single voltage |
| Contact Adjustability:  |
| Actuation point not adjustable and deactuation point not adjustable                     |
| Contact Stimulus Rating:  |
| -1.80 actuation point inches of mercury and -1.00 deactuation point inches of mercury   |
| Contact Voltage Rating In Volts:  |
| 30.0 dc at altitude single voltage  |
| Media For Which Designed:   |
| Liquid  |
| Style Designator:   |
| Cylindrical w/mounting lugs   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |

--

## NSN 5930-01-109-0759

Pressure Switch - Page 2 of 2



| _  |    | •• | • • |     |     |   |    |
|----|----|----|-----|-----|-----|---|----|
| וו | em | ш  | 112 | rız | 211 | n | ٠. |
|    |    |    |     |     |     |   |    |

No

Fiig:

A048b0