

View Online at <https://aerobasegroup.com/nsn/5930-01-109-5921>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.375 inches single mounting facility

**Overall Height:**

1.281 inches

**Overall Width:**

1.281 inches

**Shaft Diameter:**

0.250 inches 1st actuator 0.125 inches 2nd actuator

**Shaft Length:**

0.375 inches 1st actuator 0.500 inches 2nd actuator

**Individual Section Quantity:**

2

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

2 each section rear

**Throw Quantity:**

3 each section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Features Provided:**

Variable resistor

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

115.0 ac at sea level 28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

3 1st actuator

**Shaft Type:**

Round all actuators

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Makes before breaks each section rear

**Switch Actuator Positioning Increment:**

60.0 degrees 1st actuator

**Switch Actuator Stop Device Type:**

Fixed stop 1st actuator

**Contact Load Current Rating:**

500.0 milliamperes resistive load ac at sea level 1.5 amperes resistive load dc at sea level

**Precious Material And Location:**

Contact and rotor surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0