

View Online at <https://aerobasegroup.com/nsn/5930-01-109-5923>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Overall Height:

1.281 inches

Overall Width:

1.281 inches

Shaft Diameter:

0.250 inches 1st actuator 0.125 inches 2nd actuator

Shaft Length:

0.375 inches 1st actuator 0.500 inches 2nd actuator

Individual Section Quantity:

2

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Variable resistor

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level 28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

3 1st actuator

Shaft Type:

Round w/through hole 1st actuator round 2nd actuator

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

60.0 degrees 1st actuator

Switch Actuator Stop Device Type:

Fixed stop 1st actuator

Contact Load Current Rating:

500.0 milliamperes resistive load ac at sea level 1.5 amperes resistive load dc at sea level

Precious Material And Location:

Contact and rotor surfaces silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0