

View Online at <https://aerobasegroup.com/nsn/5930-01-110-3282>

**Thread Length:**

0.292 inches single mounting facility and 0.332 inches single mounting facility

**Overall Length:**

2.270 inches

**First Flat Length:**

0.750 inches single actuator

**Flat Height:**

0.098 inches single actuator and 0.100 inches single actuator

**Shaft Diameter:**

0.124 inches single actuator and 0.125 inches single actuator

**Shaft Length:**

1.264 inches single actuator

**Overall Diameter:**

0.765 inches

**Nonturn Device Radius:**

0.245 inches at 3: 00 o'clock and 0.275 inches at 3: 00 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Pin at 3: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section front

**Throw Quantity:**

3 single section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Rotor Through Connection Quantity:**

1 single section

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

60.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

250.0 milliamperes resistive load dc at sea level and 20.0 milliamperes inductive load dc at sea level

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0