

View Online at <https://aerobasegroup.com/nsn/5930-01-110-7093>

**Overall Length:**

1.760 inches

**Outside Diameter:**

0.195 inches all connections and 0.205 inches all connections

**Overall Height:**

0.480 inches

**Overall Width:**

1.000 inches

**Body Length:**

1.000 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.145 inches and 0.152 inches

**Longest Horizontal Distance Between Mounting Centers:**

Between 0.709 inches and 0.729 inches

**Longest Vertical Distance Between Mounting Centers:**

Between 0.709 inches and 0.729 inches

**Pressure Switch Type:**

Differential

**Operating Temperature Rating:**

Between -45.6 degrees celsius and 70.0 degrees celsius

**Mounting Method:**

Base and unthreaded hole

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, double make, momentary action

**Sensing Element Burst Pressure:**

8.00 pounds per square inch gage

**Terminal Type:**

Quick disconnect, female

**Contact Load Current Rating:**

10.0 milliamperes resistive load single voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

0.10 actuation point inches of water and 0.50 actuation point inches of water and 0.10 deactuation point inches of water

**Contact Voltage Rating In Volts:**

30.0 dc at sea level single voltage

**Pressure Connector Type:**

Barbed, unthreaded external all connections

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0