

View Online at <https://aerobasegroup.com/nsn/5930-01-110-7093>

Overall Length:

1.760 inches

Outside Diameter:

0.195 inches all connections and 0.205 inches all connections

Overall Height:

0.480 inches

Overall Width:

1.000 inches

Body Length:

1.000 inches

Unthreaded Mounting Hole Diameter:

Between 0.145 inches and 0.152 inches

Longest Horizontal Distance Between Mounting Centers:

Between 0.709 inches and 0.729 inches

Longest Vertical Distance Between Mounting Centers:

Between 0.709 inches and 0.729 inches

Pressure Switch Type:

Differential

Operating Temperature Rating:

Between -45.6 degrees celsius and 70.0 degrees celsius

Mounting Method:

Base and unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, double make, momentary action

Sensing Element Burst Pressure:

8.00 pounds per square inch gage

Terminal Type:

Quick disconnect, female

Contact Load Current Rating:

10.0 milliamperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

0.10 actuation point inches of water and 0.50 actuation point inches of water and 0.10 deactuation point inches of water

Contact Voltage Rating In Volts:

30.0 dc at sea level single voltage

Pressure Connector Type:

Barbed, unthreaded external all connections

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0