

View Online at <https://aerobasegroup.com/nsn/5930-01-110-7111>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Weatherproof

Overall Length:

0.531 inches

Overall Height:

1.417 inches

Overall Width:

0.492 inches

Bushing Length:

0.312 inches

Body Length:

0.531 inches

Body Width:

0.492 inches

Body Height:

0.354 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

0.214 inches

Actuator Height:

0.425 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Actuator Position-locking Relationship:

Up position locked in and out and down position locked in and out

Actuator Color:

Natural single actuator

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

End Application:

4920-01-088-2443

Mounting Surface To Terminal End Distance:

0.580 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes resistive ac

Special Features:

Epoxy sealed terminals

Precious Material And Location:

Contacts and terminal surfaces gold

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0