

View Online at <https://aerobasegroup.com/nsn/5930-01-110-7112>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

0.789 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

Overall Height:

0.755 inches

Overall Width:

0.250 inches

Body Length:

0.789 inches

Body Width:

0.250 inches

Body Height:

0.665 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.087 inches

Actuator Style:

Leaf

Actuator Free Position Height:

0.330 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

1650-00-056-7172

Inclosure Type:

Hermetically sealed

Mounting Method:

Threaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

7.0 ounces

Actuator Movement:

Between 0.030 pretravel inches and 0.003 overtravel inches and 0.006 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.000 amperes inductive dc and 1.000 amperes lamp dc and 4.000 amperes resistive ac and 2.000 amperes inductive ac and 500.000 milliamperes lamp ac

Special Features:

60.000 in. Min lg wire lead terminals

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 wire lead

Specification Data:

81349-mil-s-8805/8 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0