

View Online at <https://aerobasegroup.com/nsn/5930-01-110-7112>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

0.789 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.375 inches

**Overall Height:**

0.755 inches

**Overall Width:**

0.250 inches

**Body Length:**

0.789 inches

**Body Width:**

0.250 inches

**Body Height:**

0.665 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

0.087 inches

**Actuator Style:**

Leaf

**Actuator Free Position Height:**

0.330 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

1650-00-056-7172

**Inclosure Type:**

Hermetically sealed

**Mounting Method:**

Threaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

1.0 ounces

**Switch Actuating Force:**

7.0 ounces

**Actuator Movement:**

Between 0.030 pretravel inches and 0.003 overtravel inches and 0.006 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

4.000 amperes resistive dc and 2.000 amperes inductive dc and 1.000 amperes lamp dc and 4.000 amperes resistive ac and 2.000 amperes inductive ac and 500.000 milliamperes lamp ac

**Special Features:**

60.000 in. Min lg wire lead terminals

**Test Data Document:**

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

3 wire lead

**Specification Data:**

81349-mil-s-8805/8 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0