

View Online at <https://aerobasegroup.com/nsn/5930-01-110-9545>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.940 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Overall Height:

1.185 inches

Overall Width:

0.687 inches

Body Length:

1.940 inches

Body Width:

0.687 inches

Body Height:

0.950 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.139 inches

Actuator Length:

0.967 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

1.188 inches

Actuator Roller Diameter:

0.370 inches

Actuator Roller Width:

0.150 inches

Maximum Voltage Rating In Volts:

480.0 ac

End Application:

Los angeles class ssn (688), usns stalwart class tagos, forrestal class cv, emory s. Land class as, oliver perry class ffg, john macdonald class tags-51, mars class t-afs 1, safeguard class ars, blue ridge class lcc-19, iwo jima class lph.

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

0.5 ounces

Criticality Code Justification:

Feat

Switch Actuating Force:

3.5 ounces

Actuator Movement:

Between 0.062 overtravel inches and 0.085 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

25.000 amperes resistive ac

Special Features:

Weapon system essential

Terminal Type And Quantity:

3 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0