## NSN 5930-01-110-9584

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-110-9584

Overall Length:
5.188 inches
Overall Width:
2.812 inches
Body Height:
2.750 inches
Unthreaded Mounting Hole Diameter:
0.281 inches
Longest Horizontal Distance Between Mounting Centers:
2.406 inches
Shortest Horizontal Distance Between Mounting Centers:
0.656 inches
Longest Vertical Distance Between Mounting Centers:
3.281 inches
End Application:
Switch thermo
Pressure Switch Type:
Gage
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Electrical access port
Contact Action Stimulus:
Increase
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:
Isosceles triangle
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Terminal Type:
Screw
Contact Load Current Rating:
9.6 amperes inductive load fourth voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+10.00/+180.00 actuation point pounds per square inch gage and +10.00/+180.00 deactuation point pounds per square inch gage
Contact Adjustment Type:
External deactuation point screw and external actuation point screw

**Contact Voltage Rating In Volts:** 

550.0 dc at sea level third voltage

## NSN 5930-01-110-9584

Pressure Switch - Page 2 of 2



Pressure Conn	ector Type:
---------------	-------------

Plain, threaded internal single connection

**Thread Series Designator:** 

Npt single pressure connection

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0