NSN 5930-01-110-9822

Thermostatic Switch - Page 1 of 2

Gas



View Online at https://aerobasegroup.com/nsn/5930-01-110-9822

Hazardous Locations/environmental Protection:
Dustproof and watertight
Overall Length:
4.750 inches
Overall Height:
8.563 inches
Overall Width:
2.094 inches
Body Height:
2.938 inches
Unthreaded Mounting Hole Diameter:
0.188 inches
Distance Between Mounting Facility Centers:
5.250 inches
End Application:
Misc parts 19278
Tempurature Sensing Element Type:
Bulb
Operating Tempurature Rating:
Between -10.0 degrees fahrenheit and 245.0 degrees fahrenheit
Mounting Method:
Bracket and unthreaded hole
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Screw
Contact Load Current Rating:
9.6 amperes resistive load fourth voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+140.00/+215.00 actuation point degrees fahrenheit and +135.00/+213.00 deactuation point degrees fahrenheit
Contact Adjustment Type:
External deactuation point shaft and external actuation point shaft
Contact Voltage Rating In Volts:
550.0 dc at sea level third voltage
Media For Which Designed:

NSN 5930-01-110-9822 Thermostatic Switch - Page 2 of 2



Precious Material And Location:
Contacts silver
Precious Material:
Silver
Style Designator:
Rectangular
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0