

View Online at <https://aerobasegroup.com/nsn/5930-01-110-9822>

Hazardous Locations/environmental Protection:

Dustproof and watertight

Overall Length:

4.750 inches

Overall Height:

8.563 inches

Overall Width:

2.094 inches

Body Height:

2.938 inches

Unthreaded Mounting Hole Diameter:

0.188 inches

Distance Between Mounting Facility Centers:

5.250 inches

End Application:

Misc parts 19278

Temperature Sensing Element Type:

Bulb

Operating Temperature Rating:

Between -10.0 degrees fahrenheit and 245.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

9.6 amperes resistive load fourth voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+140.00/+215.00 actuation point degrees fahrenheit and +135.00/+213.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point shaft and external actuation point shaft

Contact Voltage Rating In Volts:

550.0 dc at sea level third voltage

Media For Which Designed:

Gas

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0