## NSN 5930-01-111-0720



Push Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-01-111-0720 **Body Style:** Panel mount **Overall Length:** 0.750 inches **Overall Height:** 2.710 inches **Overall Width:** 0.750 inches **Body Length:** 0.688 inches **Body Width:** 0.750 inches **Body Height:** 2.620 inches **Case Material:** Metal **Actuator Length:** 0.620 inches **Actuator Style:** Rectangular **Actuator Height:** 0.090 inches **Actuator Width:** 0.620 inches **Actuator Color:** Natural single actuator **Actuator Inscription:** Lamp test single actuator **Maximum Voltage Rating In Volts:** 115.0 ac and 28.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Panel **Features Provided:** Rfi shielding

## **Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

### **Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

#### **Precious Material And Location:**

Contacts silver

# NSN 5930-01-111-0720

Push Switch - Page 2 of 2



Termin:	al Tyne	And (	Quantity:
	ai ivbe	Allu V	zuannıv.

3 socket, integrated wire termination

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0