## NSN 5930-01-111-1364

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-111-1364

**Thread Class:** 

3a single threaded bushing

**Thread Length:** 

0.535 inches single threaded bushing and 0.565 inches single threaded bushing

**Hazardous Locations/environmental Protection:** 

General purpose-nema type 1

**Overall Length:** 

Between 15.670 inches and 16.700 inches

**Body Diameter:** 

0.320 centimeters

**Body Length:** 

4.000 inches

**End Application:** 

Ntn/oy-7 (v) 1 05869

**Tempurature Sensing Element Type:** 

Internal sensor

Width Across Flats:

0.690 inches

**Operating Tempurature Rating:** 

Between 0.0 degrees fahrenheit and 350.0 degrees fahrenheit

**Mounting Method:** 

Threaded bushing

Features Provided:

Hermetically sealed case

Thready Qty Per Inch (tpi):

20 single threaded bushing

**Contact Action Stimulus:** 

Increase

Thread Size:

0.438 inches single threaded bushing

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

**Terminal Type:** 

Wire lead

**Contact Load Current Rating:** 

1.0 amperes resistive load third voltage and 500.0 milliamperes inductive load third voltage and 200.0 milliamperes lamp load third voltage

**Contact Adjustability:** 

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:** 

170.00 actuation point degrees fahrenheit and 140.00 deactuation point degrees fahrenheit

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level second voltage

## **NSN 5930-01-111-1364** Thermostatic Switch - Page 2 of 2

Frequency In Hertz:



60.0 first voltage
Media For Which Designed:
Gas
Style Designator:
Cylindrical w/flange
Test Data Document:
81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unf single threaded bushing
Specification Data:
81349-mil-s-24236/11 government specification
Shelf Life:
N/a
Unit Of Measure:
<del>-</del>
Demilitarization:
No
Fiig:
A048b0