NSN 5930-01-111-1374

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-111-1374

Body Style:
Bushing mount
Hazardous Locations/environmental Protection:
Weatherproof
Overall Length:
1.336 inches
Overall Height:
2.359 inches
Overall Width:
0.734 inches
Bushing Length:
0.469 inches
Body Length:
1.336 inches
Body Width:
0.734 inches
Case Material:
Plastic
Actuator Style:
Round
Actuator Diameter:
0.240 inches
0.240 inches Actuator Height:
Actuator Height:
Actuator Height: 0.687 inches
Actuator Height: 0.687 inches Actuator Position-action Relationship:
Actuator Height: 0.687 inches Actuator Position-action Relationship: Up position maintained and down position momentary
Actuator Height: 0.687 inches Actuator Position-action Relationship: Up position maintained and down position momentary Actuator Color:
Actuator Height: 0.687 inches Actuator Position-action Relationship: Up position maintained and down position momentary Actuator Color: Natural single actuator
Actuator Height: 0.687 inches Actuator Position-action Relationship: Up position maintained and down position momentary Actuator Color: Natural single actuator Maximum Voltage Rating In Volts:
Actuator Height: 0.687 inches Actuator Position-action Relationship: Up position maintained and down position momentary Actuator Color: Natural single actuator Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc
Actuator Height: 0.687 inches Actuator Position-action Relationship: Up position maintained and down position momentary Actuator Color: Natural single actuator Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc End Application:
Actuator Height: 0.687 inches Actuator Position-action Relationship: Up position maintained and down position momentary Actuator Color: Natural single actuator Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc End Application: Weapon systems-ticonderoga class cg (47); spruance class dd (963)
Actuator Height: 0.687 inches Actuator Position-action Relationship: Up position maintained and down position momentary Actuator Color: Natural single actuator Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc End Application: Weapon systems-ticonderoga class cg (47); spruance class dd (963) Mounting Surface To Terminal End Distance:
Actuator Height: 0.687 inches Actuator Position-action Relationship: Up position maintained and down position momentary Actuator Color: Natural single actuator Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc End Application: Weapon systems-ticonderoga class cg (47); spruance class dd (963) Mounting Surface To Terminal End Distance: 1.203 inches
Actuator Height: 0.687 inches Actuator Position-action Relationship: Up position maintained and down position momentary Actuator Color: Natural single actuator Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc End Application: Weapon systems-ticonderoga class cg (47); spruance class dd (963) Mounting Surface To Terminal End Distance: 1.203 inches Inclosure Type:
Actuator Height: 0.687 inches Actuator Position-action Relationship: Up position maintained and down position momentary Actuator Color: Natural single actuator Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc End Application: Weapon systems-ticonderoga class cg (47); spruance class dd (963) Mounting Surface To Terminal End Distance: 1.203 inches Inclosure Type: Fully enclosed
Actuator Height: 0.687 inches Actuator Position-action Relationship: Up position maintained and down position momentary Actuator Color: Natural single actuator Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc End Application: Weapon systems-ticonderoga class cg (47); spruance class dd (963) Mounting Surface To Terminal End Distance: 1.203 inches Inclosure Type: Fully enclosed Mounting Method:

Thready Qty Per Inch (tpi):

NSN 5930-01-111-1374

Toggle Switch - Page 2 of 2



Thread	Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

25.000 amperes resistive dc and 15.000 amperes inductive dc and 7.000 amperes lamp dc and 25.000 amperes resistive ac and 15.000 amperes inductive ac and 7.000 amperes lamp ac

Special Features:

Weapon system essential

Test Data Document:

81349-mil-s-8834 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Specification Data:

96906-ms14001 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0