## NSN 5930-01-111-1375

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-111-1375

Body Style:
Bushing mounted
Hazardous Locations/environmental Protection:
Weatherproof
Overall Length:
3.440 inches
Overall Height:
2.500 inches
Overall Width:
1.150 inches
Actuator Style:
Roller plunger
Actuator Free Position Height:
2.140 inches
Actuator Roller Diameter:
0.500 inches
Actuator Roller Width:
0.180 inches
Housing Diameter:
1.150 inches
Housing Length:
1.300 inches
Housing Bushing Length:
0.870 inches
Maximum Voltage Rating In Volts:
28.0 dc
Inclosure Type:
Hermetically sealed
Mounting Method:
Unthreaded hole
Features Provided:
Actuator seal
Thread Size:
0.750 inches
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Switch Actuating Force:
144.0 inch-ounces

**Actuator Movement:** 

Between 0.050 pretravel inches and 0.250 overtravel inches and 0.015 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:** 

5.000 amperes resistive dc and 2.000 amperes inductive dc

## NSN 5930-01-111-1375

Sensitive Switch - Page 2 of 2



Inread	Series	Designator
Unef		

**Terminal Type And Quantity:** 

1 connector, receptacle

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0