## NSN 5930-01-111-3608

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-111-3608 **Thread Class:** 2a single mounting facility Thread Length: 0.280 inches single mounting facility **Hazardous Locations/environmental Protection:** Dustproof **Overall Length:** 1.640 inches **Shaft Diameter:** 0.120 inches single actuator **Shaft Length:** 0.720 inches single actuator **Overall Diameter:** 0.520 inches **Individual Section Quantity: End Application:** F111 sim memr 53855 **Switch Contact Basic Design:** Nonpile-up symmetrical Pole Quantity: 1 single section rear **Throw Quantity:** 10 single section rear **Mounting Method:** Threaded bushing single mounting facility **Features Provided:** Metallic inclosure **Thread Size:** 0.250 inches single mounting facility **Contact Voltage Rating In Volts:** 115.0 ac at sea level **Switch Actuator Indexing Position Quantity:** 10 single actuator **Shaft Type:** Round single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Breaks before makes single section rear **Switch Actuator Positioning Increment:** 

36.0 degrees single actuator

## NSN 5930-01-111-3608

Rotary Switch - Page 2 of 2



## **Switch Actuator Stop Device Type:** Adjustable stop single actuator **Contact Load Current Rating:** 150.0 milliamperes resistive load ac at sea level **Precious Material And Location:** Contacts and terminals gold and contacts silver **Precious Material:** Gold and silver Style Designator: Snap or line **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a **Unit Of Measure:** Demilitarization:

No Fiig: A052b0