

View Online at <https://aerobasegroup.com/nsn/5930-01-111-4353>

**Hazardous Locations/environmental Protection:**

Moisture proof

**Overall Length:**

1.188 inches

**Overall Height:**

0.369 inches

**Body Diameter:**

0.630 inches

**Body Height:**

0.349 inches

**Unthreaded Mounting Hole Diameter:**

0.109 inches

**Distance Between Mounting Facility Centers:**

0.937 inches

**End Application:**

T2c oper flgt

**Temperature Sensing Element Type:**

Internal sensor

**Mounting Method:**

Bracket and unthreaded hole

**Features Provided:**

Tamper proof cap

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, momentary action

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

10.0 amperes resistive load first voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

194.00 actuation point degrees fahrenheit and 174.00 deactuation point degrees fahrenheit

**Contact Voltage Rating In Volts:**

240.0 ac at sea level first voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Disc w/flange

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0