

View Online at <https://aerobasegroup.com/nsn/5930-01-111-4607>

**Thread Class:**

2b all threaded hole

**Inside Diameter:**

0.160 inches all connections

**Overall Length:**

4.880 inches

**Outside Diameter:**

0.190 inches all connections

**Overall Width:**

3.120 inches

**Body Diameter:**

3.120 inches

**Body Length:**

3.060 inches

**Distance Between Mounting Facility Centers:**

1.624 inches

**Pressure Switch Type:**

Differential

**Operating Temperature Rating:**

Between 15.6 degrees celsius and 71.0 degrees celsius

**Mounting Method:**

Base and threaded hole

**Features Provided:**

Tamper proof cap

**Thready Qty Per Inch (tpi):**

32 all threaded hole

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

15.00 inches of water

**Thread Size:**

0.190 inches all threaded hole

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

5.0 amperes resistive load second voltage and 3.0 amperes inductive load second voltage

**Contact Adjustability:**

Deactuation point adjustable, preset and actuation point adjustable, preset

**Contact Adjustment Range:**

+0.15/+4.00 actuation point inches of water and +0.15/+4.00 deactuation point inches of water

**Contact Adjustment Type:**

External deactuation point screw and external actuation point screw

**Contact Stimulus Rating:**

0.09 differential point inches of water

**Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

**Pressure Connector Type:**

Barbed, unthreaded external all connections

**Media For Which Designed:**

Gas

**Style Designator:**

Cylindrical w/mounting lugs

**Thread Series Designator:**

Unc all threaded hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0