

View Online at <https://aerobasegroup.com/nsn/5930-01-111-5395>

Thread Class:

2a single mounting facility

Thread Length:

0.414 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.472 inches

Overall Height:

1.605 inches

Overall Width:

1.200 inches

First Flat Length:

0.500 inches single actuator

Flat Height:

0.206 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.586 inches single actuator

Nonturn Device Radius:

0.500 inches at 12: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 12: 00 o'clock

End Application:

Training dev 23259

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

10 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

120.0 dc at sea level

Shaft Flat/slot Angular Location:

180.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

10 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Printed circuit

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load dc at sea level

Style Designator:

Square wafer, panel mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0