NSN 5930-01-111-7672

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-111-7672

Hazardous Locations/environmental Protection:
General purpose-nema type 1
Overall Height:
2.250 inches
Body Diameter:
5.750 inches
End Application:
Donut servicing 53918
Pressure Switch Type:
Gage
Mounting Method:
Outlet connection
Thready Qty Per Inch (tpi):
18 single pressure connection
Contact Action Stimulus:
Increase
Thread Size:
0.250 inches single pressure connection
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
500.0 milliamperes resistive load fourth voltage
Contact Adjustability:
Deactuation point not adjustable, manual reset and actuation point adjustable
Deactuation point not adjustable, manual reset and actuation point adjustable Contact Adjustment Range:
Contact Adjustment Range:
Contact Adjustment Range: +5.00/+100.00 actuation point pounds per square inch gage
Contact Adjustment Range: +5.00/+100.00 actuation point pounds per square inch gage Contact Stimulus Rating:
Contact Adjustment Range: +5.00/+100.00 actuation point pounds per square inch gage Contact Stimulus Rating: 3.50 differential point pounds per square inch gage
Contact Adjustment Range: +5.00/+100.00 actuation point pounds per square inch gage Contact Stimulus Rating: 3.50 differential point pounds per square inch gage Contact Voltage Rating In Volts:
Contact Adjustment Range: +5.00/+100.00 actuation point pounds per square inch gage Contact Stimulus Rating: 3.50 differential point pounds per square inch gage Contact Voltage Rating In Volts: 480.0 ac at sea level first voltage
Contact Adjustment Range: +5.00/+100.00 actuation point pounds per square inch gage Contact Stimulus Rating: 3.50 differential point pounds per square inch gage Contact Voltage Rating In Volts: 480.0 ac at sea level first voltage Pressure Connector Type:
Contact Adjustment Range: +5.00/+100.00 actuation point pounds per square inch gage Contact Stimulus Rating: 3.50 differential point pounds per square inch gage Contact Voltage Rating In Volts: 480.0 ac at sea level first voltage Pressure Connector Type: External seat-gasket seal, threaded external single connection
Contact Adjustment Range: +5.00/+100.00 actuation point pounds per square inch gage Contact Stimulus Rating: 3.50 differential point pounds per square inch gage Contact Voltage Rating In Volts: 480.0 ac at sea level first voltage Pressure Connector Type: External seat-gasket seal, threaded external single connection Thread Series Designator:
Contact Adjustment Range: +5.00/+100.00 actuation point pounds per square inch gage Contact Stimulus Rating: 3.50 differential point pounds per square inch gage Contact Voltage Rating In Volts: 480.0 ac at sea level first voltage Pressure Connector Type: External seat-gasket seal, threaded external single connection Thread Series Designator: Npt single pressure connection
Contact Adjustment Range: +5.00/+100.00 actuation point pounds per square inch gage Contact Stimulus Rating: 3.50 differential point pounds per square inch gage Contact Voltage Rating In Volts: 480.0 ac at sea level first voltage Pressure Connector Type: External seat-gasket seal, threaded external single connection Thread Series Designator: Npt single pressure connection Shelf Life:
Contact Adjustment Range: +5.00/+100.00 actuation point pounds per square inch gage Contact Stimulus Rating: 3.50 differential point pounds per square inch gage Contact Voltage Rating In Volts: 480.0 ac at sea level first voltage Pressure Connector Type: External seat-gasket seal, threaded external single connection Thread Series Designator: Npt single pressure connection Shelf Life: N/a

No

NSN 5930-01-111-7672Pressure Switch - Page 2 of 2



Fiig:

A048b0