

View Online at <https://aerobasegroup.com/nsn/5930-01-111-7680>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Weatherproof

Overall Length:

0.510 inches

Overall Height:

1.395 inches

Overall Width:

0.275 inches

Bushing Length:

0.300 inches

Body Length:

0.510 inches

Body Width:

0.275 inches

Body Height:

0.430 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

0.115 inches

Actuator Height:

0.410 inches

Actuator Position-action Relationship:

Up position momentary and down position maintained

Actuator Color:

Silver single actuator

Maximum Voltage Rating In Volts:

125.0 ac and 28.0 dc

End Application:

Jss/rocc 05869

Mounting Surface To Terminal End Distance:

0.685 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 2.000 amperes inductive ac and 1.000 amperes lamp ac

Special Features:

Epoxy sealed terminals; panel sealed

Precious Material And Location:

Contacts and terminal surfaces gold

Test Data Document:

81349-mil-s-83731 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 printed circuit

Specification Data:

81349-mil-s-83731/9 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0