

View Online at <https://aerobasegroup.com/nsn/5930-01-111-9973>

Overall Length:

1.260 inches

Overall Height:

0.605 inches

Body Diameter:

0.640 inches

Mounting Slot Width:

Between 0.133 inches and 0.147 inches

Body Height:

Between 0.295 inches and 0.315 inches

Unthreaded Mounting Hole Diameter:

Between 0.133 inches and 0.147 inches

Distance Between Mounting Facility Centers:

Between 0.930 inches and 0.944 inches

Operating Temperature Rating:

575.0 degrees fahrenheit

Mounting Method:

Slot and unthreaded hole

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

500.0 milliamperes resistive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

375.00 deactuation point degrees fahrenheit and 410.00 actuation point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0