Code Indicating Wheel Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-112-0045

| view Online at https://aeiobasegroup.com/hsi//3930-01-112-0043 |
|--|
| Hazardous Locations/environmental Protection: |
| Corrosion resistant and dust resistant |
| Overall Length: |
| 2.160 inches |
| Overall Height: |
| 1.695 inches |
| Overall Width: |
| 1.200 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.100 inches single mounting facility |
| Individual Section Quantity: |
| 4 |
| Longest Horizontal Distance Between Mounting Centers: |
| 1.990 inches single mounting facility |
| Longest Vertical Distance Between Mounting Centers: |
| 0.900 inches single mounting facility |
| Operating Tempurature Range: |
| -20.0/+75.0 degrees celsius |
| Mounting Method: |
| Bracket single mounting facility and unthreaded hole single mounting facility |
| Actuator Type: |
| Thumbwheel all actuators |
| Contact Voltage Rating In Volts: |
| 28.0 dc at sea level |
| Mounting Facility Pattern: |
| Four position rectangular single mounting facility |
| Switch Actuator Indexing Position Quantity: |
| 16 all actuators |
| Terminal Type: |
| Tab, solder lug |
| Contact Load Current Rating: |
| 125.0 milliamperes resistive load dc at sea level |
| Readout Indicator Marking: |
| 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, a, b, c, d, e, f each section |
| Contact Arrangement Truth Table: |
| Binary code with complement, 2 pole - 16 positions with 2 commons each section |
| Color: |
| White each indicator marking |
| Precious Material And Location: |
| Circuit disc surfaces gold |
| Precious Material: |
| Gold |
| |

AeroBase

Group

Style Designator:

Rectangular inline indicating

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0