
## NSN 5930-01-112-0860

Push Switch - Page 1 of 2



**Thread Class:** 

2a

Body Style:

Bushing mounted

## **Overall Length:**

1.131 inches

#### **Overall Height:**

2.984 inches

#### **Overall Width:**

0.625 inches

**Bushing Length:** 

Between 0.234 inches and 0.266 inches

**Body Length:** 

0.725 inches

#### Body Width:

0.625 inches

## **Body Height:**

0.672 inches

#### Actuator Diameter:

Between 0.077 inches and 0.079 inches

#### Actuator Height:

Between 2.016 inches and 2.046 inches

#### Maximum Voltage Rating In Volts:

28.0 dc

#### **End Application:**

6625-01-036-7821

#### Inclosure Type:

Fully enclosed

#### Mounting Method:

Threaded bushing

#### Thready Qty Per Inch (tpi):

32

## Thread Size:

0.250 inches

## Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, one position momentary single switch unit

## Contact Load Current Rating At Maximum Rated Voltage:

400.000 milliamperes resistive dc

## Precious Material And Location:

Contact surfaces gold and contact surfaces silver

### Unable To Decode:

Unable to decode and unable to decode



# NSN 5930-01-112-0860

Push Switch - Page 2 of 2

**Thread Series Designator:** 

Unef

### Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A053a0

