# NSN 5930-01-112-1301

Push Switch - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5930-01-112-1301

#### **Body Style:**

Panel mount

#### Hazardous Locations/environmental Protection:

Moisture proof and shock proof

#### **Overall Length:**

0.755 inches

#### **Overall Height:**

3.060 inches

#### **Overall Width:**

0.755 inches

#### **Body Length:**

0.755 inches

#### Body Width:

0.755 inches

## Body Height:

2.250 inches

## Case Material:

Case Material.

Metal

#### Actuator Length:

0.755 inches

#### Actuator Style:

Rectangular

#### Actuator Width:

0.755 inches

#### Actuator Color:

Amber single actuator and red single actuator

#### **Illuminated Actuator Color:**

Amber single actuator and red single actuator

#### **Actuator Inscription:**

Alarm ack/air dis prs alm single actuator

#### Illuminated Actuator Color Sequence:

Upper half of actuator amber lower half of actuator red

#### Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

#### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Panel

#### **Features Provided:**

Actuator seal

#### **Nonpile-up Contact Arrangement:**

4 pole, double throw, one position momentary single switch unit



Push Switch - Page 2 of 2



## Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc and 5.000 amperes resistive ac and 2.500 amperes

inductive ac and 1.500 amperes lamp ac

## Special Features:

Horizontal split lens

## Precious Material And Location:

Contact surfaces gold and contacts silver

## Unable To Decode:

Unable to decode and unable to decode

## Terminal Type And Quantity:

19 pin

Shelf Life:

N/a

### Unit Of Measure:

---

## Demilitarization:

No

#### Fiig:

A053a0