## NSN 5930-01-112-1321

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-112-1321

Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Moisture proof and shock proof
Overall Length:
0.755 inches
Overall Height:
3.060 inches
Overall Width:
0.755 inches
Body Length:
0.755 inches
Body Width:
0.755 inches
Body Height:
2.250 inches
Case Material:
Metal
Actuator Length:
0.755 inches
Actuator Style:
Rectangular
Actuator Width:
0.755 inches
Actuator Color:
Amber single actuator and red single actuator
Illuminated Actuator Color:
Amber single actuator and red single actuator
Actuator Inscription:
Tube 8 alm ack/alarm single actuator
Illuminated Actuator Color Sequence:
Upper half of actuator amber lower half of actuator red
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
4 note double throw one position momentary single switch unit

## NSN 5930-01-112-1321

Push Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac and 1.500 amperes lamp ac

cioco amporco reciente de ana 2:000 amporco madente de
inductive ac and 1.500 amperes lamp ac
Special Features:
Horizontal split lens
Precious Material And Location:
Contact surfaces gold and contacts silver
Unable To Decode:
Unable to decode and unable to decode
Terminal Type And Quantity:
19 pin
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0