

View Online at <https://aerobasegroup.com/nsn/5930-01-112-1330>

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Moisture proof and shock proof

Overall Length:

0.755 inches

Overall Height:

3.060 inches

Overall Width:

0.755 inches

Body Length:

0.755 inches

Body Width:

0.755 inches

Body Height:

2.250 inches

Case Material:

Metal

Actuator Length:

0.755 inches

Actuator Style:

Rectangular

Actuator Width:

0.755 inches

Actuator Color:

Amber single actuator and red single actuator

Illuminated Actuator Color:

Amber single actuator and red single actuator

Actuator Inscription:

Tube 11 alm ack/alarm single actuator

Illuminated Actuator Color Sequence:

Upper half of actuator amber lower half of actuator red

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

4 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac and 1.500 amperes lamp ac

Special Features:

Horizontal split lens

Precious Material And Location:

Contact surfaces gold and contacts silver

Unable To Decode:

Unable to decode and unable to decode

Terminal Type And Quantity:

19 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0