

View Online at <https://aerobasegroup.com/nsn/5930-01-112-5213>

Thread Class:

2a single mounting facility

Thread Length:

0.297 inches single mounting facility and 0.327 inches single mounting facility

Overall Length:

1.703 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.092 inches single actuator and 0.096 inches single actuator

Shaft Diameter:

0.125 inches single actuator

Shaft Length:

0.376 inches single actuator

Overall Diameter:

Between 0.745 inches and 0.755 inches

Nonturn Device Radius:

0.250 inches at 12:00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Pin at 12:00 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

6 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.5 amperes resistive load dc at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0