

View Online at <https://aerobasegroup.com/nsn/5930-01-112-5213>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.297 inches single mounting facility and 0.327 inches single mounting facility

**Overall Length:**

1.703 inches

**First Flat Length:**

0.250 inches single actuator

**Flat Height:**

0.092 inches single actuator and 0.096 inches single actuator

**Shaft Diameter:**

0.125 inches single actuator

**Shaft Length:**

0.376 inches single actuator

**Overall Diameter:**

Between 0.745 inches and 0.755 inches

**Nonturn Device Radius:**

0.250 inches at 12:00 o'clock

**Individual Section Quantity:**

2

**Nonturn Device Type:**

Pin at 12:00 o'clock

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

6 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

5.5 amperes resistive load dc at sea level

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0