

View Online at <https://aerobasegroup.com/nsn/5930-01-112-5484>

**Thread Class:**

2b single mounting facility

**Overall Length:**

2.563 inches

**Overall Height:**

6.000 inches

**Overall Width:**

6.000 inches

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.938 inches single actuator

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

3.000 inches single mounting facility

**Shortest Horizontal Distance Between Mounting Centers:**

1.500 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

3.000 inches single mounting facility

**Shortest Vertical Distance Between Mounting Centers:**

1.500 inches single mounting facility

**End Application:**

Meter module 00062

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section rear

**Throw Quantity:**

62 single section rear

**Mounting Method:**

Threaded hole single mounting facility

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.164 inches single mounting facility

**Contact Voltage Rating In Volts:**

120.0 ac at sea level

**Mounting Facility Pattern:**

Four position diamond single mounting facility

**Switch Actuator Indexing Position Quantity:**

62 single actuator

**Shaft Type:**

Round single actuator

**Terminal Type:**

Turret

**Contact Switching Action:**

Breaks before makes single section rear

**Contact Load Current Rating:**

15.0 amperes resistive load ac at sea level

**Precious Material And Location:**

Contacts and wipers silver

**Precious Material:**

Silver

**Style Designator:**

Tap, square frame

**Thread Series Designator:**

Unc single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0